

RACKCONSOLE-PRO 17HR-FR-USB

KVM add-ons, Article number A3200088



The RackConsole-PRO is a key drawer and enables direct access to servers mounted in a rack. The key drawer is a stand-alone device and compatible with many G&D devices.

SCOPE OF DELIVERY

Quantity	Description	Article number
1	PowerCable-2 Standard cable 2m	A6300057
1	DVI-I zu DVI-D AdapterInLine 17760P für RackConsole	Z0006128
1	DVI-I zu DVI-A VGA AdapterInLine 17790P für RackConsole	Z0006129
1	Karton RackConsole mit Zubehör e37747w, 823x560x120, 2.40 EB	VP100014
1	Safety instructions flyer - FCC class B	A9100371

DETAILS

VIDEO

- Max. resolution:
 - 1920 × 1200 at 60 Hz (digital and analog)
 - 2560 × 1600 at 60 Hz (digital, scaled)
- Color mode: digital 24 bit
- Variable video inputs:
 - DVI-I (digital/analog)
 - DisplayPort
 - HDMI

DEVICE

- Display: TFT LCD with LED backlight
- USB port for keyboard and mouse
- Transparent USB 3.0 interface on front panel
- Optimized industrial video panel
- High-quality and durable control elements
- Robust case and components especially designed for use in server rooms or industrial environments
- Optimal protection of controls and panel when folded up
- Smooth-running mechanism with nevertheless firm locking for opening and closing the display lid
- Reinforced and precisely tuned telescopic rails for stable installation in racks of any depth
- Special robust energy chain to protect cables
- Internal power pack for main power supply

WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible



FEATURES

OPERATION FEATURES

- Mouse control via built-in touchpad
- On-screen display for operation and configuration
- Automatic power on/off when opening/closing the display

EXTENSIONS

DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply

TECHNICAL DATA

General	Product group	KVM add-ons
	Product Family	RackConsole-Pro
	Power Supply	Redundancy without load balancing
Input options	USB mouse	yes
	USB keyboard	yes
Maintenance	Update via	no update possibility
Housing	Material	Steel sheet
	Width ca.	483 mm
	Height ca.	44 mm
	Depth ca.	628 mm
	IP protection class	IP20
	Weight ca.	13.46 kg
Operating conditions	Operating environment temperature	5 °C to 45 °C
	Operating air humidity, non-condensing	20 % to 60 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,000 m
	Storage environment temperature	-20 °C to 60 °C
	Storage air humidity, non-condensing	15 % to 70 %

	MTBF	50,000 h at 25°C
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) TAA compliant (see downloads) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
Power supply 1	Quantity	1
	Type	Internal
	Input voltage	100-240 VAC
	Input frequency	60-50 Hz
	Current consumption	1.1-0.6 A
	Power consumption idle	0.58-0.43 W
	Power consumption max.	49.2-48.4 W
	Heat output idle	0.58-0.43 W
	Heat output max.	44.7-44.3 W
Power supply 2	Quantity	1
	Type	External
	Input voltage	12 VDC
	Current consumption	4.2 A
	Power consumption idle	0.48 W
	Power consumption max.	48 W



	Heat output idle	0.48 W
	Heat output max.	43.5 W

ACCESSORY PRODUCTS

Image	Description	Article number
	PowerCable-3 Standard cable 3m Cable to connect the power supply type Germany	A6300066
	PowerCable-5 Standard cable 5m Cable to connect the power supply type Germany	A6300065

MORE VARIANTS

Description	Article number
RackConsole-PRO 17HR-BE-F-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Belgium French, with touchpad	A3200084
RackConsole-PRO 17HR-CH-D-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Swiss German, with touchpad	A3200085
RackConsole-PRO 17HR-DE-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout German, with touchpad	A3200086
RackConsole-PRO 17HR-ES-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Spanish, with touchpad	A3200087
RackConsole-PRO 17HR-Nord-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Nordic, with touchpad	A3200089
RackConsole-PRO 17HR-RU-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout Russian, with touchpad	A3200090
RackConsole-PRO 17HR-UK-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout UK English, with touchpad	A3200091
RackConsole-PRO 17HR-US-USB Keyboard drawer for rack assembly 19", display 17" wide screen, keyboard layout US English, with touchpad	A3200092

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +1-833-928-1976
Fax: +1-833-928-1976
E-Mail: sales.us@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com