



# CAT-RS232-CPU

KVM extenders, Article number A1990006



The signal extender system CAT-RS232 extends/receives RS232 signals. The system consists of a computer module (transmitter) and a console module (receiver) and uses CAT-x cables to transmit RS232 signals up to 280 m.

## SCOPE OF DELIVERY

| Quantity | Description                    | Article number |
|----------|--------------------------------|----------------|
| 1        | RS232-M/F-2 cable RS232 2m     | A6300023       |
| 1        | PowerCable-2 Standard cable 2m | A6300057       |



## DETAILS

### SIGNALS

- Transparent bidirectional RS232 (max. 115,200 bps)

### TRANSMISSION

- The transmission distance is up to 280 meters over CAT

### DEVICE

- External power supply

### WARRANTY

- A 3-year, free of charge product guarantee

## TECHNICAL DATA

|              |                                 |                                                     |
|--------------|---------------------------------|-----------------------------------------------------|
| General      | Product group                   | KVM extenders                                       |
|              | Product Family                  | CAT-RS232-CPU/CON                                   |
|              | Power Supply                    | no redundancy                                       |
| Transmission | Number of transmission channels | 1                                                   |
|              | Redundant transmission channels | no redundant KVM transmission                       |
|              | Range                           | 280 m (AWG22)<br>260 m (AWG24)<br>200 m (AWG26)     |
|              | Medium                          | CAT7<br>CAT6<br>CAT5e                               |
| Serial       | Standard                        | RS232                                               |
|              | Transparent transmission        | yes                                                 |
|              | Data rate                       | max. 115,200 bps                                    |
|              | Signals                         | TxD<br>RxD<br>DTR<br>DSR<br>RTS<br>CTS<br>DCD<br>RI |
| Maintenance  | Update via                      | no update possibility                               |
| Housing      | Material                        | anodised aluminium                                  |
|              | Width ca.                       | 55 mm                                               |

|                      |                                            |                                                                                                                                                                                                                                                                   |
|----------------------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      | Height ca.                                 | 24 mm                                                                                                                                                                                                                                                             |
|                      | Depth ca.                                  | 104 mm                                                                                                                                                                                                                                                            |
|                      | IP protection class                        | IP20                                                                                                                                                                                                                                                              |
|                      | Weight ca.                                 | 0.12 kg                                                                                                                                                                                                                                                           |
| Operating conditions | Operating temperature                      | 5 °C to 45 °C                                                                                                                                                                                                                                                     |
|                      | Operating air humidity, non-condensing     | 20 % to 80 %                                                                                                                                                                                                                                                      |
|                      | Area of application                        | Indoor use                                                                                                                                                                                                                                                        |
|                      | Maximum operating altitude above sea level | 3,048 m                                                                                                                                                                                                                                                           |
|                      | Storage temperature                        | -10 °C to 55 °C                                                                                                                                                                                                                                                   |
|                      | Storage air humidity, non-condensing       | 15 % to 85 %                                                                                                                                                                                                                                                      |
|                      | Conformities                               | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
| Power supply         | Quantity                                   | 1                                                                                                                                                                                                                                                                 |
|                      | Type                                       | External                                                                                                                                                                                                                                                          |
|                      | Input voltage                              | 5 VDC                                                                                                                                                                                                                                                             |
|                      | Current consumption                        | 0.07 A                                                                                                                                                                                                                                                            |

## ACCESSORY PRODUCTS

| Image                                                                             | Description                                                                             | Article number |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|----------------|
|  | <b>RS232-M/F-3 cable RS232 3m</b><br>Cable to connect a serial device                   | A6300024       |
|  | <b>RS232-M/F-5 cable RS232 5m</b><br>Cable to connect a serial device                   | A6300025       |
|  | <b>PowerCable-3 Standard cable 3m</b><br>Cable to connect the power supply type Germany | A6300066       |
|  | <b>PowerCable-5 Standard cable 5m</b><br>Cable to connect the power supply type Germany | A6300065       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)