

# DL-VISION(S)-AR-CON

KVM extenders, Article number A1220048



The KVM extenders of the DL-Vision series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated fiber connection (up to 10,000 m) uncompressed, pixel-perfect and without any latency or loss. An extender system consists of a computer module (CPU) and a console module (CON). The DL-Vision series supports DualLink-DVI for high-resolution video up to 2560 × 1600 (60 Hz) or 4096 × 2160 (30 Hz).

## SCOPE OF DELIVERY

| Quantity | Description                             | Article number |
|----------|-----------------------------------------|----------------|
| 2        | PowerCable-2 Standard cable 2m          | A6300057       |
| 1        | 19" RM-Set-436-1RU-Type2                | A7000011       |
| 1        | Java CP Launcher                        | A8200052       |
| 1        | Safety instructions flyer - FCC class B | A9100371       |

## DETAILS

### VIDEO

- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings
- Resolution up to  
2560 × 1600 @ 60 Hz

### SIGNALS

- Transparent audio signals (stereo, analog)
- Transparent RS232 (max. 230,400 bps)

### TRANSMISSION

- The transmission distance is up to 10,000 meters over fiber singlemode optics, incl. transmission module(s)/ SFP transceiver(s)

### DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- MultiChannel variants (MC): Modules for multi-monitor workplaces with multi-channel video
  - MC mode uses the full bandwidth for each video channel, whereby a separate transmission line is required for each channel

### WARRANTY

- A 3-year, free of charge product guarantee
- For an additional fee guarantee extension possible

## FEATURES

### SECURITY FEATURES

- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- Freeze function: If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- Redundant internal power packs
- Redundant network interface

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Operation via multilingual on-screen display (OSD) and hotkeys
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness
- Local console at the computer module allows on-site operation, including all video channels
- Exclusive or concurrent operation: The KVM extender allows computer control both remotely and locally. When an input is detected, the extender automatically locks the competing console. The lock is lifted after a preset timeout if no further input is detected. A key combination can activate exclusive operation, immediately disabling the competing console. Another key combination restores shared control.

## TECHNICAL DATA

|               |                                 |                                   |
|---------------|---------------------------------|-----------------------------------|
| General       | Product group                   | KVM extenders                     |
|               | Product Family                  | DL-Vision                         |
|               | Power Supply                    | Redundancy without load balancing |
| Input options | USB mouse                       | yes                               |
|               | USB keyboard                    | yes                               |
|               | PS/2 mouse                      | yes                               |
|               | PS/2 keyboard                   | yes                               |
| Transmission  | Number of transmission channels | 1                                 |
|               | Redundant transmission channels | no redundant KVM transmission     |
|               | Range                           | 10,000 m (9/125µm, OS1)           |
|               | Laser class                     | Class 1                           |
|               | Type of interface               | LC-Duplex                         |
|               | Wavelength                      | 1,310 nm                          |
|               | Medium                          | Fiber SM                          |
|               | Data rate                       | 10 Gbit/s                         |
| Video output  | Quantity                        | 1                                 |
|               | Format                          | DualLink DVI                      |
|               | Colour depth                    | 24 bit                            |
|               | Pixel rate ca.                  | 25 MPixel/s to 330 MPixel/s       |

|        |                              |                                                                                                                 |
|--------|------------------------------|-----------------------------------------------------------------------------------------------------------------|
|        | Vertical frequency           | 20 Hz to 120 Hz                                                                                                 |
|        | Horizontal frequency         | 25 kHz to 185 kHz                                                                                               |
|        | Exemplary resolutions        | 2560 × 1600 (60 Hz)<br>4096 × 2160 (30 Hz)<br>2048 × 2160 (60 Hz)<br>2048 × 2048 (60 Hz)<br>3840 × 2160 (30 Hz) |
|        | General Notes                | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.     |
|        | Supported industry standards | Enhanced Display Data Channel (E-DDC)<br>Display Data Channel Command Interface (DDC/CI)                        |
| Audio  | Transmission type            | Stereo<br>Transparent                                                                                           |
|        | Resolutions                  | 24 bit digital                                                                                                  |
|        | Sampling rate                | up to 96 kHz                                                                                                    |
|        | Bandwidth                    | 22 kHz                                                                                                          |
|        | Audio support                | Analog                                                                                                          |
| Serial | Standard                     | RS232                                                                                                           |
|        | Transparent transmission     | yes                                                                                                             |
|        | Data rate                    | max. 230,400 bps                                                                                                |

|                      |                                        |                                               |
|----------------------|----------------------------------------|-----------------------------------------------|
|                      | Signals                                | TxD<br>RxD<br>DTR<br>DSR<br>RTS<br>CTS<br>DCD |
| Network              | Quantity                               | 2                                             |
|                      | Medium                                 | CAT5<br>CAT6<br>CAT7                          |
|                      | Data rate                              | 10 Mbit/s<br>100 Mbit/s<br>1 Gbit/s           |
| Maintenance          | Update via                             | ConfigPanel (Network)                         |
|                      | Serviceport settings                   | 230400bps (8/N/1)                             |
| Housing              | Material                               | anodised aluminium                            |
|                      | Width ca.                              | 436 mm                                        |
|                      | Height ca.                             | 44 mm                                         |
|                      | Depth ca.                              | 284 mm                                        |
|                      | IP protection class                    | IP20                                          |
|                      | Weight ca.                             | 2.81 kg                                       |
| Operating conditions | Operating temperature                  | 5 °C to 45 °C                                 |
|                      | Operating air humidity, non-condensing | 0 % to 80 %                                   |
|                      | Area of application                    | Indoor use                                    |

|              |                                            |                                                                                                                                                                                                                                                                   |
|--------------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|              | Maximum operating altitude above sea level | 3,048 m                                                                                                                                                                                                                                                           |
|              | Storage temperature                        | -10 °C to 55 °C                                                                                                                                                                                                                                                   |
|              | Storage air humidity, non-condensing       | 0 % to 85 %                                                                                                                                                                                                                                                       |
|              | MTBF                                       | 170,000 h at 25°C                                                                                                                                                                                                                                                 |
|              | Conformities                               | CE compliant (see downloads)<br>UKCA compliant (see downloads)<br>FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads) |
|              |                                            |                                                                                                                                                                                                                                                                   |
| Power supply | Quantity                                   | 2                                                                                                                                                                                                                                                                 |
|              | Type                                       | Internal                                                                                                                                                                                                                                                          |
|              | Input voltage                              | 100-240 VAC                                                                                                                                                                                                                                                       |
|              | Input frequency                            | 60-50 Hz                                                                                                                                                                                                                                                          |
|              | Current consumption                        | 0.5-0.2 A                                                                                                                                                                                                                                                         |
|              | Power consumption max.                     | 16.6-17.2 W                                                                                                                                                                                                                                                       |
|              | Heat output max.                           | 13.6-14.2 W                                                                                                                                                                                                                                                       |

## ACCESSORY PRODUCTS

| Image                                                                             | Description                                                                             | Article number |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|----------------|
|  | <b>USB-Service-2 cable 2m</b><br>Cable for system updates and configuration             | A6200103       |
|  | <b>PowerCable-3 Standard cable 3m</b><br>Cable to connect the power supply type Germany | A6300066       |
|  | <b>PowerCable-5 Standard cable 5m</b><br>Cable to connect the power supply type Germany | A6300065       |

## RELATED PRODUCTS

| Description                                                                                        | Article number |
|----------------------------------------------------------------------------------------------------|----------------|
| <b>DL-Vision(S)-AR-CPU</b><br>Computer module to extend Dual-Link-DVI signals via fiber singlemode | A1210066       |

## MORE VARIANTS

| Description                                                                                              | Article number |
|----------------------------------------------------------------------------------------------------------|----------------|
| <b>DL-Vision(S)-ARU2+CON</b><br>Console module to receive Dual-Link-DVI signals via fiber singlemode     | A1220215       |
| <b>DL-Vision(S)-MC2-AR-CON</b><br>Console module to receive Dual-Link-DVI signals via fiber singlemode   | A1220052       |
| <b>DL-Vision(S)-MC2-ARU2+CON</b><br>Console module to receive Dual-Link-DVI signals via fiber singlemode | A1220216       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)