

U2-LAN-04-CON

KVM extenders, Article number A1120378



With the U2-LAN-04, you can integrate high-speed USB 2.0 into your KVM-over-IP matrix installation and add extensive USB functionality to the ControlCenter-IP or ControlCenter-IP-XS. U2-LAN-04 end devices can be paired with KVM-over-IP extenders and switched synchronously. Alternatively, synchronous switching can also be carried out via IP-Control-API. Device class filtering lets you exclude or block special USB classes via the ControlCenter-IP. Note: MatrixGuard not compatible with U2-LAN devices.

SCOPE OF DELIVERY

Quantity	Description	Article number
1	Safety instructions flyer - FCC class B	A9100371

DETAILS

SIGNALS

- USB 2.0 with Hi-Speed (separate transmission line, transparent, all USB classes)

TRANSMISSION

- KVM-over-IP™ via IP-based networks (layer 3)
- Transmission distance between two active network components is up to 100 meters over CAT cables

WARRANTY

- A 2-year, free of charge product guarantee

TECHNICAL DATA

General	Product group	KVM extenders
	Product Family	U2-LAN
	KVM matrix system component	Console module (digital)
	Power Supply	no redundancy
Transmission	Number of transmission channels	1
	Redundant transmission channels	no redundant KVM transmission
	Range	100 m
	Medium	CAT7 CAT6 CAT5e
	Data rate	1 Gbit/s
USB	Separate USB transmission port	yes
	Specification	USB 2.0
	Medium	CAT5e CAT6 CAT7
	Transmission rate	max. 480 Mbit/s (Hi-Speed)
	Range	max. 100 m
	Power (output)	600 mA (HighPower)
	USB classes	All
Housing	Material	anodised aluminium

	Width ca.	100 mm
	Height ca.	26 mm
	Depth ca.	76 mm
	IP protection class	IP20
	Weight ca.	0.38 kg
Operating conditions	Operating environment temperature	0 °C to 50 °C
	Operating air humidity, non-condensing	20 % to 80 %
	Area of application	Indoor use
	Maximum operating altitude above sea level	3,048 m
	Storage environment temperature	-20 °C to 70 °C
	Storage air humidity, non-condensing	10 % to 90 %
	MTBF	3,200,000 h at 25°C
	Conformities	CE compliant (see downloads) UKCA compliant (see downloads) FCC compliant (see manual) EAC compliant (see downloads) RoHS compliant (see downloads) WEEE (reg. no. DE30763240) REACH compliant (see downloads)
Power supply	Quantity	1
	Type	External
	Input voltage	24 VDC
	Current consumption	1 A

ACCESSORY PRODUCTS

Image	Description	Article number
	CaseMount-Set U2-LAN Screws & brackets for fitting devices of the U2-LAN series in a DeviceCarrier frame	A7000054

CONTACT

WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

TECHNICAL SALES

Tel.: +49 271 23872-333
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung
Obere Leimbach 9 | 57074 Siegen | NRW |
Deutschland

Tel.: +49 271 23872-0
Fax: +49 271 23872-120
E-Mail: sales@gdsys.com

US OFFICE

G&D North America Inc.
4540 Kendrick Plaza Drive | Suite 100
Houston, TX 77032 | United States

Tel.: +1-346-620-4362
E-Mail: sales.us@gdsys.com

MIDDLE EAST OFFICE

Guntermann & Drunck GmbH
Dubai Studio City | DSC Tower
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178
E-Mail: sales.me@gdsys.com

APAC OFFICE

Guntermann & Drunck GmbH
60 Anson Road #17-01
Singapore 079914

Tel.: +65 9685 8807
E-Mail: sales.apac@gdsys.com