

# VISIONXS-CPU-C-DP-HR-DH-U2

KVM extenders, Article number A1110581



The matrix-compatible KVM extenders of the VisionXS-DP-HR series extend keyboard, video, and mouse signals, as well as other peripheral data (e.g., audio and USB), via a dedicated CAT or fiber connection (up to 10,000 m). An extender system consists of a computer module (CPU) and a compatible console module (CON). Computers can be controlled in near real-time – both in extender and matrix applications. The VisionXS-DP-HR series supports DisplayPort 1.1 for high-resolution video up to 2560 x 1600 (60 Hz) or 4096 x 2160 (30 Hz). Video data is processed pixel-perfectly and offers excellent hand-eye coordination, thanks to bluedec™ – G&D's advanced, multi-stage, lossless compression technology.

## SCOPE OF DELIVERY

| Quantity | Description                             | Article number |
|----------|---|----------------|
| 1        | Safety instructions flyer - FCC class B | A9100371       |
| 1        | Power supply usage flyer                | A9100409       |
| 1        | DP1.4-Cable-M/M-2 SK13357 2m            | A6300173       |
| 1        | USB-AM/BM-2 cable USB 2m                | A6300113       |

## DETAILS

### VIDEO

- bluedec™ – advanced developed multi-stage compression for best video quality and practically latency-free transmission. This method enables pixel-perfect video transmission with efficient bandwidth use.
- The end devices can be flexibly combined with each other, even if they process different video signals (Mix & Match)
- EDID data utilization from the workplace monitor
- Flexible EDID profile options for optimized monitor settings
- Resolution up to  
2560 × 1600 @ 60 Hz,  
4096 × 2160 @ 30 Hz

### SIGNALS

- Embedded stereo audio (DisplayPort Digital, 2 channel LPCM, AC3, DTS, sampling rate up to 192 kHz)
- GenericUSB support for USB classes HID (Human Interface Device), SmartCard and mass storage
- The product allows the use of a GenericUSB device via a console module. For this, both the used console module and the used computer module must support the use of a GenericUSB device.
- USB 2.0 with Hi-Speed (separate transmission line, transparent, all USB classes)

### TRANSMISSION

- The transmission distance is up to 140 meters over CAT

### DEVICE

- Improved security through physical separation between workplaces and computers
- Access to standard interfaces of the computer, with no software installation required
- Compact design for space-saving installation within a VisionXS DeviceCarrier (1 or 3 RU)
- The devices are compatible with the ControlCenter-Digital and ControlCenter-Compact series (matrix operation) and other end devices for computer and workplace connections (extender operation)
- PowerPack not included in the scope of delivery
- DT variant: Optional redundant power supply via an internal power unit for high reliability
- Fanless variant: fanless model

### WARRANTY

- A 3-year, free of charge product guarantee



- For an additional fee guarantee extension possible

## FEATURES

### SECURITY FEATURES

- Bootloader, operating system, and firmware form a "Trusted Computing Platform" with automatic integrity checks during system startup
- Integrated Trusted Platform Module (TPM) protects all access and configuration data from being spied on or tampered with by third parties
- Console modules do not store security-relevant information such as login credentials, which could be extracted in the event of device loss
- Early detection of security incidents or unusual activities through continuous monitoring via Syslog, monitoring, and SNMP
- Comprehensive rights management and user administration, allowing precise control over which user can access which resources
- Option for activatable access protection (default operating mode in matrix systems), in which authentication is required before accessing computer sources
- Support for external directory services (Active Directory, Radius, LDAP) to meet company security policies
- To comply with individual password policies and improve security, password complexity can be configured system-wide
- Configurable login options, such as displaying terms of use or setting the maximum acceptable number of failed login attempts, can enhance system security
- Auto Backup Function: Automates backups at user-defined intervals and replaces manual intervention – ensuring reliable, timely data protection without the need for continuous monitoring
- Freeze function: If the video signal is lost, the last displayed image is frozen and highlighted with a colored frame and timer
- 2-Factor-Authentication (2FA) – is integrated by default in KVM extenders and enhances security by requiring a second, possession-based factor during user authentication:
  - The traditional password authentication is combined with a time-limited, single-use code (Time-Based-One-Time-Password - TOTP)
  - You can choose between using the internal authentication server provided in the device or an external directory service
  - Authenticator apps or hardware token can be used
  - This additional layer of protection prevents unauthorized access and ensures the highest level of security, particularly in sensitive IT environments

### OPERATION FEATURES

- Ready for operation out of the box, no additional configuration required
- Permanent keyboard/mouse emulation ensures a stable system
- Compatibility with special USB-HID input devices

- Operation via multilingual on-screen display (OSD) and hotkeys
- Configuration and update via the multilingual HTML5 web interface “Config Panel 21” (Java-free)
- Support of DDC/CI (Display Data Channel / Command Interface) to enable centralized software-side control of monitor settings such as brightness

## EXTENSIONS

### DEVICE

- External power supply via external 12V power pack or G&D-MultiPower, providing a central and redundant power supply
- Device mounting via G&D 19” DeviceCarrier for VisionXS (1 or 3 RU)

### SYSTEM EXTENSION

- Transm. Redundancy Option (comparable to UC/CON-2): Devices are prepared for transmission redundancy without additional hardware and can be activated via software feature key.
  - Computer modules can connect to various counterparts, such as compatible console modules or KVM matrix switches
  - Console modules can connect to different counterparts, such as compatible computer modules or KVM matrix switches, with switching controlled via hotkey or automatically depending on configuration
  - U2 variants do not support the Transm. Redundancy Option as the 2nd transmission interface is used for the transmission of USB 2.0 data
- You can integrate the matrix-compatible extenders into a complete installation with a ControlCenter-Compact or ControlCenter-Digital, even at a later point in time. This provides you with even greater flexibility through the possibility of distributed access – and the existing components can continue to be used.

## PANELS AND CONNECTORS

### FRONT



| Aperture designation | Design             | Description                      |
|----------------------|--------------------|----------------------------------|
| USB CPU              | USB-B socket 2.0   | Connection to computer - USB 2.0 |
| DP CPU 1             | DisplayPort socket | Connection to computer - Video   |
| DP CPU 2             | DisplayPort socket | Connection to computer - Video   |

### BACK



| Aperture designation | Design            | Description  |
|----------------------|-------------------|--|
| Transmission 1       | RJ45 socket       | Data transmission to console module or matrix switch (CAT) |
| Transmission 2       | RJ45 socket       | Separate USB transmission to console module (CAT)          |
| Service              | Micro-USB socket  | Port for service purposes                                  |
| Network              | RJ45 socket       | Port for IP network  |
| Power                | Mini-DIN 4 socket | Power supply DC  |

## TECHNICAL DATA

|              |                                 |  |
|--------------|---------------------------------|--|
| General      | Product group                   | KVM extenders                                  |
|              | Product Family                  | VisionXS                                       |
|              | KVM matrix system component     | Computer module (digital)                      |
|              | Power Supply                    | no redundancy                                  |
| Transmission | Number of transmission channels | 2  |
|              | Redundant transmission channels | no redundant KVM transmission                  |
|              | Range                           | 140 m (AWG22)<br>100 m (AWG24)<br>80 m (AWG26) |
|              | Medium                          | CAT5e<br>CAT6<br>CAT7                          |
|              | Data rate                       | 1 Gbit/s                                       |
| Video input  | Quantity                        | 2  |
|              | Format                          | DisplayPort 1.1 (HBR)                          |
|              | Colour depth                    | 24 bit   |
|              | Pixel rate ca.                  | 25 MPixel/s to 300 MPixel/s                    |
|              | Vertical frequency              | 24 Hz to 120 Hz                                |
|              | Horizontal frequency            | 25 kHz to 185 kHz                              |

|       |                                |  |
|-------|--------------------------------|--|
|       | Exemplary resolutions          | 4096 × 2160 (30 Hz)<br>4096 × 2160 (25 Hz)<br>4096 × 2160 (24 Hz)<br>3840 × 2160 (30 Hz)<br>3840 × 2160 (25 Hz)<br>3840 × 2160 (24 Hz)<br>2560 × 1600 (60 Hz)<br>2048 × 2048 (60 Hz)<br>1920 × 1200 (60 Hz)<br>1920 × 1080 (60 Hz) |
|       | General Notes                  | Further VESA and CTA standardised resolutions possible within pixel rate and horizontal/vertical frequency.  |
|       | Supported industry standards   | Display Data Channel Command Interface (DDC/CI)<br>Extended Display Identification Data (EDID)   |
| Audio | Transmission type              | 2-channel LPCM<br>Stereo<br>DTS<br>AC3   |
|       | Resolutions                    | 24 bit<br>20 bit<br>16 bit   |
|       | Sampling rate                  | up to 192 kHz  |
|       | Audio support                  | Digital Embedded   |
| USB 1 | Separate USB transmission port | no   |
|       | Specification                  | USB 2.0  |
|       | GenericUSB support             | 1 device   |
|       | Medium                         | Embedded   |
|       | Transmission rate              | max. 25 Mbit/s (Full Speed)  |

|             |                                |   |
|-------------|--------------------------------|---|
|             | USB classes                    | Mass Storage (MSC / UMS)<br>Human Interface Device (HID)<br>SmartCard |
| USB 2       | Separate USB transmission port | yes   |
|             | Specification                  | USB 2.0   |
|             | Medium                         | CAT5e<br>CAT6<br>CAT7   |
|             | Transmission rate              | max. 480 Mbit/s (Hi-Speed)  |
|             | Range                          | max. 100 m  |
|             | Power (output)                 | 500 mA (HighPower)  |
|             | USB classes                    | All   |
|             |                                |   |
| Network     | Quantity                       | 1   |
|             | Medium                         | CAT5<br>CAT6<br>CAT7  |
|             | Data rate                      | 10 Mbit/s<br>100 Mbit/s   |
| Maintenance | Update via                     | ConfigPanel (Network)   |
|             | Serviceport settings           | 115200bps (8/N/1)   |
| Housing     | Material                       | Anodised aluminium  |
|             | Width ca.                      | 109 mm  |
|             | Height ca.                     | 31 mm   |
|             | Depth ca.                      | 184 mm  |

|                      |  |   |
|----------------------|--|---|
|                      | IP protection class                        | IP20  |
| Operating conditions | Operating environment temperature          | 5 °C to 45 °C   |
|                      | Operating air humidity, non-condensing     | 20 % to 80 %  |
|                      | Area of application                        | Indoor use  |
|                      | Maximum operating altitude above sea level | 3,048 m   |
|                      | Storage environment temperature            | -20 °C to 60 °C   |
|                      | Storage air humidity, non-condensing       | 15 % to 85 %  |
|                      | MTBF                                       | 200,000 h at 25°C   |
|                      | Conformities                               | FCC compliant (see manual)<br>TAA compliant (see downloads)<br>EAC compliant (see downloads)<br>RoHS compliant (see downloads)<br>WEEE (reg. no. DE30763240)<br>REACH compliant (see downloads)<br>CE compliant (see downloads)<br>UKCA compliant (see downloads) |
| Power supply         | Quantity                                   | 1   |
|                      | Type                                       | External  |
|                      | Input voltage                              | 12 VDC  |
|                      | Current consumption                        | 1 A   |

## MORE VARIANTS

| Description   | Article number |
|---|----------------|
| <b>VisionXS-CPU-C-DP-HR</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110272       |
| <b>VisionXS-CPU-C-DP-HR-A</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110273       |
| <b>VisionXS-CPU-C-DP-HR-A-U</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110274       |
| <b>VisionXS-CPU-C-DP-HR-A-U2</b><br>Computer module to extend DisplayPort signals via CAT cable   | A1110578       |
| <b>VisionXS-CPU-C-DP-HR-AR-DT</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110276       |
| <b>VisionXS-CPU-C-DP-HR-AR-U-DT</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110277       |
| <b>VisionXS-CPU-C-DP-HR-AR-U2-DT</b><br>Computer module to extend DisplayPort signals via CAT cable                                       | A1110577       |
| <b>VisionXS-CPU-C-DP-HR-DH</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line         | A1110512       |
| <b>VisionXS-CPU-C-DP-HR-DH-A</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line       | A1110515       |
| <b>VisionXS-CPU-C-DP-HR-DH-A-U</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line     | A1110513       |
| <b>VisionXS-CPU-C-DP-HR-DH-A-U2</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line    | A1110580       |
| <b>VisionXS-CPU-C-DP-HR-DH-AR-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line   | A1110517       |
| <b>VisionXS-CPU-C-DP-HR-DH-AR-U-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line | A1110516       |

| Description  | Article number |
|--|----------------|
| <b>VisionXS-CPU-C-DP-HR-DH-AR-U2-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line | A1110579       |
| <b>VisionXS-CPU-C-DP-HR-DH-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line       | A1110519       |
| <b>VisionXS-CPU-C-DP-HR-DH-U</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line        | A1110514       |
| <b>VisionXS-CPU-C-DP-HR-DH-U-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line     | A1110518       |
| <b>VisionXS-CPU-C-DP-HR-DH-U2-DT</b><br>Dual head computer module (CAT cable) to extend 2 DisplayPort signals using 1 transmission line    | A1110582       |
| <b>VisionXS-CPU-C-DP-HR-DT</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110278       |
| <b>VisionXS-CPU-C-DP-HR-U</b><br>Computer module to extend DisplayPort signals via CAT cable   | A1110275       |
| <b>VisionXS-CPU-C-DP-HR-U-DT</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110279       |
| <b>VisionXS-CPU-C-DP-HR-U2</b><br>Computer module to extend DisplayPort signals via CAT cable  | A1110583       |
| <b>VisionXS-CPU-C-DP-HR-U2-DT</b><br>Computer module to extend DisplayPort signals via CAT cable   | A1110584       |

# CONTACT

## WE ARE HERE FOR YOU!

If you have any further questions, we are looking forward to advising you on your individual project requirements.

### TECHNICAL SALES

Tel.: +1-833-928-1976  
Fax: +1-833-928-1976  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### HEADQUARTERS

Guntermann & Drunck GmbH Systementwicklung  
Obere Leimbach 9 | 57074 Siegen | NRW |  
Deutschland

Tel.: +49 271 23872-0  
Fax: +49 271 23872-120  
E-Mail: [sales@gdsys.com](mailto:sales@gdsys.com)

### US OFFICE

G&D North America Inc.  
4540 Kendrick Plaza Drive | Suite 100  
Houston, TX 77032 | United States

Tel.: +1-346-620-4362  
E-Mail: [sales.us@gdsys.com](mailto:sales.us@gdsys.com)

### MIDDLE EAST OFFICE

Guntermann & Drunck GmbH  
Dubai Studio City | DSC Tower  
12th Floor, Office 1208 | Dubai, UAE

Tel.: +971 4 5586178  
E-Mail: [sales.me@gdsys.com](mailto:sales.me@gdsys.com)

### APAC OFFICE

Guntermann & Drunck GmbH  
60 Anson Road #17-01  
Singapore 079914

Tel.: +65 9685 8807  
E-Mail: [sales.apac@gdsys.com](mailto:sales.apac@gdsys.com)